



AGM BATTERIES

6V: 100~200Ah

12V: 36~200Ah



FML Series For High Cycle Use

Type	Nominal Voltage (V)	Rated Capacity(Ah)				Dimensions(mm)				Weight Appox (kg)	Terminal type
		20HR	10HR	5HR	1HR	Length	Width	Height	Total Height		
		1.75V/C	1.80V/C	1.75V/C	1.75V/C						
3-FML-100	6	100	92	80	60	195	170	206	210	16	M2
3-FML-150	6	150	138	120	90	260	180	247	250	25	M3
3-FML-200	6	200	184	160	120	323	178	226	231	31	M5
6-FML-36	12	36	33.1	28.8	21.6	195	131	155	169	11.4	M1
6-FML-38	12	38.0	34.2	30.4	22.8	198.0	166.0	170.0	170.0	13.2	M1
6-FML-56	12	56.0	51.4	44.8	33.6	229.0	138.0	212.0	217.0	19.0	M1
6-FML-65	12	65.0	61.0	52.0	39.0	350.0	167.0	177.0	177.0	21.5	M2
6-FML-85	12	85	78.2	68	51	260	169	211	216	25.0	M1
6-FML-100	12	100.0	92.0	80.0	60.0	407.0	174.0	208.0	236.0	32.6	M3
6-FML-110	12	110	101	88	66	329	172	215	222	33.5	M5
6-FML-120	12	120.0	110.0	96.0	72.0	407.0	174.0	208.0	236.0	36.5	M3
6-FML-150	12	150	138	120	90	532	207	216	221	50	M5
6-FML-200	12	200.0	184.0	160.0	120.0	523.0	240.0	225.0	230.0	62.5	M3



Naicon Srl Via il Caravaggio, 25 Trecella
 1-20060 Pozzuolo Martesana – Milano (Italy)
 Tel. +39 02 95.003.1 Fax + 39 02 95.003.313
 www.naicon.com email: naicon@naicon.com