

# SERIE VISION



		D.VISION109+ D.VISION09	D.VISION112+ D.VISION12	D.VISION118+ D.VISION18
Alimentazione			220-240V~/50Hz/1P	
Capacità nominale	Btu/kW	9000(3500~11000)/ 2,6	12000(4700~14700)/ 3,5	18000(11570~20130)/ 5,3
Potenza assorbita	W	613(90~1140)	977(130~1650)	1550(560~2050)
Corrente assorbita	A	2,66(0.4~4.7)	4,24(0.6~7.2)	6,7(2.4~9)
EER		4,30	3,60	3,40
Capacità nominale	Btu/kW	10000(2800~11500)/ 2,9	13000(3640~14950)/ 3,8	19000(10580~19960)/ 5,6
Potenza assorbita	W	637(110~1080)	977(160~1560)	1500(780~2000)
Corrente assorbita	A	2,77(0.48~4.7)	4,24(0.7~6.78)	6,5(3.4~8.7)
COP		4,6	3,90	3,71
Raffr. stagionale Capacità (pdesignc)	kW	2,6	3,5	5,3
SEER/Classe Efficienza Energetica		9,3/A+++	8,5/A+++	7/A++
Risc. (clima caldo) Capacità (pdesignh)	kW	2,7	3,0	4,5
SCOP/Classe Efficienza Energetica		6,0/A+++	6,1/A+++	5,1/A+++
<b>Unità interna</b>				
Portata d'aria max. Raffr./Risc.	m3/h	483/362/303	584/477/395	730/500/420
Liv. Press.Sonora (Turbo/Alta/Med/Bassa/Mute)	dB(A)	36,5/29,0/24,0/20,0	39,5/33/25/21	43/33,5/28/22
Dimensioni (LxAxP)	mm	802x189x297	802x189x297	965x215x319
Peso netto/lordo	Kg	8,6/11,1	8,6/11,1	10,9/14,2
<b>Unità Esterna</b>				
Liv. Press.Sonora/Potenza Sonora	dB(A)	54/60	54,5/62	55,57/57
Dimensioni (LxAxP)		765x303x555	765x303x555	805*330*554
Peso netto/lordo	Kg	26,7/29,1	26,7/29,1	33,5/36,1
<b>Refrigerante</b>				
Tipo/GWP/Quantità precaricata		R32/0.62kg/675	R32/0.62kg/675	R32/1,1kg/675
<b>Tubazione gas</b>				
Lato liquido/Lato gas	Pollici	3/8"/1/4"	3/8"/1/4"	1/2"/1/4"
Max lungh. Tubazioni/dislivello	m	25/10	25/10	30/20